

ACCURIOPRINT C4065 SPECIFICATIONS

RETHINK OPTIONS

AccurioPrint C4065

Type	Console
Color availability	Color
Scanning resolution	600 dpi x 600 dpi
Writing resolution	Equivalent to 3600 dpi x 2400 dpi
Print/Copy Speed	A4 Simplex: 66 ppm
	A3 Simplex: 37 ppm
	217-360 g/m ² 45 A4/26 A3
Gradation	256
Paper Sizes	330.2 x 487.7 mm 330.2 x 860 mm (max.duplex) 330.2 x 1300 mm (max. simplex)
Standard Paper Tray Capacity	1500 sheets A4 80 gsm
Magnification	25 - 400%, in 0.1% steps
System memory	8 GB
Warm-up Time	390 seconds or less
First copy out time (Color/Monochrome)	6.5 seconds or less(A4) colour
	4.0 seconds or less (A4) B&W
Scan speed (A4)	Single-sided 140 opm ^{a3} Duplex 280 opm ^{a1}
Envelope Printing	Standard
Main Unit Size (WxDxH) mm	84.65 x 35.55 x 58.19 inches (2,150 x 903 x 1478 mm) (main unit + DF-713 + LU-202m + FS-532+IC-607)
Power consumption	3840 W or less(Main body)
Duty Cycle	7,02,000 ²
Average Monthly Print Volume	Upto 26,500 (A4)

KONICA MINOLTA IMAGE CONTROLLER IC-607

Architecture	Internal
OS	Linux
CPU	Intel Pentium C4400
Clock speed	3.2 GHz
RAM std	16 GB
HDD	2 TB (2 x 1TB)
Page-description language	Adobe® PostScript® 3; PDF v1.7; TIFF (v6); PPML v2.2
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11~10.15

FIERY IMAGE CONTROLLER IC-419

Architecture	Internal
OS	Linux
CPU	Intel® Pentium® Processor G4400
Clock speed	3.2 GHz
RAM std	8 GB
HDD	500 GB
Page-description language	Adobe® PostScript® Levels 1, 2, 3, APPE 5, Microsoft Office document formats: doc, docx, xls,xlsx, ppt, pptx, pub (via Hot Folders)
Applicable OS	Windows 8.1/10; Windows Server 2012/R2/2016/2019; Mac OS X 10.11-14

DF-713 — DUAL SCAN DOCUMENT FEEDER (OPTION)

Tray Capacity	300 sheets (80 gsm)		
Original Weight Duplex	50 - 210 gsm		
Detectable Document Size	Min: 100 x 140 mm		
	Max: 297 x 432 mm		
Scan Speed by Resolution	200 dpi	Colour: Simplex 140 ipm	Duplex 280 ipm
		Monochrome: Simplex 140 ipm	Duplex 280 ipm
Scan Speed by Resolution	300 dpi	Colour: Simplex 120 ipm	Duplex 240 ipm
		Monochrome: Simplex 120 ipm	Duplex 240 ipm
Scan Speed by Resolution	400 dpi	Colour: Simplex 100 ipm	Duplex 200 ipm
		Monochrome: Simplex 100 ipm	Duplex 200 ipm
Copy Speed	600 dpi	Colour: Simplex 75 ipm	Duplex 150 ipm
		Monochrome: Simplex 80 ipm	Duplex 160 ipm

OPTIONS

KM Image Controller	IC-607
EFI Internal Controller	IC-419
Paper Feeding Unit	PF-602m
Paper feeding unit	PF-707m
PFU connection Kit	FA-502
Dehumidifier heater	HT-503
Fusing unit for envelope printing	HT-511
Large capacity feeding unit	LU-202m
Envelope printing guide for LU	MK-746
Large capacity feeding unit (banner)	LU-202XLm
Multi bypass feeding	MB-508
Banner Paper Feeder kit	MK-760
Multi bypass tray	MB-509
Intelligent Media Sensor	IM-101
Output Tray	OT-511
Stapling Unit	FS-532m
Saddle Stitcher Kit	SD-510
Punch Kit	PK-525
Post Inserter Kit	PI-502
Output Tray Unit	OT-512
Long Sheet Kit (Output)	MK-761

-All specifications refer to A4-size paper of 80 gsm quality.

-The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

-Some of the product illustrations contain optional accessories.

-Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.

-Konica Minolta does not warrant that any prices or specifications mentioned will be error-free.

-All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

-¹When using KM when using IC-607

-²Peak volume in Q Zone

-³When using DF-713, 200 dpi